

## **EDIUS 7 Support Information for Blackmagic Design NLE Hardware**

\*Please install Black Magic Design Desktop Video 9.7.x to use the NLE hardware with EDIUS 7 (Desktop Video 10 cannot be used with EDIUS 7)

1 loade install black Magic	= 00.g = 00op				(= 00:00 ::000 :	<del> </del>	
Function	Deck Link SDI	Deck Link Studio / 2	DeckLink HD Extreme 3D	Deck Link Duo	Deck Link Quad	Deck Link 4K Extreme	Intensity Pro
10-bit depth support	Yes	Yes	Yes	Yes	Yes	Yes	Only in SD format
1080p24 mode*1	Native/PsF	Native/PsF	Native/PsF	Native/PsF	Native/PsF	Native/PsF	-
2K(2048x1556) support	-	-	Yes	-	-	Yes	-
4K support	-	-	-	-	-	Yes	-
TC Input*2	Yes	Yes	Yes	Yes	Yes	Yes	-
TC Output*2	Yes	Yes	Yes	Yes	Yes	Yes	-
Capture with ANC data*3	Yes	Yes	Yes	Yes	Yes	Yes	-
Ancillary Data thru out*3	Yes	Yes	Yes	Yes	Yes	Yes	-
Stereoscopic support	-	-	Yes	-	-	Yes	-
Deck Control Support	-	-	-	-	-	-	-
External REF Input	Yes	Yes	Yes	Yes	Yes	Yes	-
Max Audio ch/bit	8ch / 24bit	8ch / 24bit	16ch / 24bit	8ch/24bit	8ch/24bit	16ch / 24bit	2ch / 24bit
Windows 8 support	Yes	Yes	Yes	Yes	Yes	Yes	Yes
A Color of State on the State of the March Devictor Control Devict							

<sup>\*1</sup> Select either mode in Black Magic Design Control Panel

<sup>\*2</sup> Timecode may not be able to I/O in several video formats. Please refer to "Supported Format" list for details.

<sup>\*3 10</sup>bit video needs to be selected in project format for ancillary data I/O.



## **EDIUS 7 Support Information for Blackmagic Design NLE Hardware**

Function	Intensity Shuttle for USB 3.0	Intensity Extreme	Ultra Studio SDI	Ultra Studio Pro USB3.0	Ultra Studio Express	Ultra Studio 4K
10-bit depth support	Yes	Only in SD format	Yes	Yes	Yes	Yes
1080p24 mode*1	-	-	Native/PsF	Native/PsF	Native/PsF	Native/PsF
1080p60/50 mode	-	-	-	-	-	-
2K(2048x1556) support	-	-	-	-	-	-
4K support	-	-	-	-	-	Yes
TC Input	-	-	Only in SD format	Yes	Yes	Yes
TC Output	-	-	-	-	Yes	Yes
Capture with ANC data*2	-	-	Yes	Yes	-	Yes
Ancillary Data thru out*2	-	-	-	-	Yes	Yes
Stereoscopic support	-	-	-	-	-	Yes
Deck Control Support	-	-	-	-	-	-
External REF Input	-	-	Yes	Yes	Yes	Yes
Max Audio ch/bit	8ch / 24bit	2ch / 24bit	8ch / 24bit	8ch / 24bit	2ch / 24 bit	16ch / 24bit
Windows 8 support	Yes	Yes	Yes	Yes	Yes	Yes

<sup>\*1</sup> Select either mode in Black Magic Design Control Panel
\*2 10bit video needs to be selected in project format for ancillary data I/O.



## **EDIUS 7 Support Information for Blackmagic Design NLE Hardware**

Function	Ultra Studio Mini Recorder	Ultra Studio Mini Monitor
10-bit depth support	Yes	Yes
1080p24 mode*1	Native/PsF	Native/PsF
1080p60/50 mode	-	-
2K(2048x1556) support	-	-
4K support	-	-
TC Input	Yes	-
TC Output	-	Only SD
Capture with ANC data*2	-	-
Ancillary Data thru out*2	-	Yes
Stereoscopic support	-	-
Deck Control Support	-	-
External REF Input	-	-
Max Audio ch/bit	16ch / 24bit	16ch / 24bit
Windows 8 support	Yes	Yes

<sup>\*1</sup> Select either mode in Black Magic Design Control Panel

<sup>\*2 10</sup>bit video needs to be selected in project format for ancillary data I/O.



## **EDIUS 7 Supported Format for Blackmagic Design NLE Hardware**

\*Please install Black Magic Design Desktop Video 9.7.x to use the NLE hardware with EDIUS 7 (Desktop Video 10 cannot be used with EDIUS 7)

H/W Model Name	H/W Model Name Interface		Supported Format	Description
DeckLink SDI	ln	SDI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i	Time code can't be fed while capturing with 1920x1080p series format.
DeckLink 3DI	Out	SDI	1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	Time code can't be output in 1920x1080p and 1280x720p series format.
		SDI	.1920x1080/29.97p, 25p, 24p, 23.98p	
	ln	HDMI	1920x1080/59.94i, 50i 1280x720/59.94p, 50p	
	""	Component	720x486/59.94i, 720x576/50i	
DeckLink Studio / 2		S-Video & Composite	720x486/59.94i, 720x576/50i	
DeckLiffk Studio / 2		SDI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i, 720x576/50i	Time code can't be output with 1920x1080p, 1920x1080i and 1280x720p series format.
	Out	Component		
	Out	HDMI	1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i, 720x576/50i	
		S-Video & Composite	720x486/59.94i, 720x576/50i	
		SDI (2D)	2048x1556/25p, 24p, 23.98p 1920x1080/59.94i, 50i 1920x1080*/59.94p, 50p, 29.97p, 25p, 24p, 23.98p 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	Time code can't be fed while capturing with 1920x1080p series format.
DeckLink HD Extreme 3D / 3D+	ln	SDI (3D)	1920x1080/59.94i, 50i 1280x720/59.94p, 50p	Time code can't be fed while capturing all formats.
	""	Component	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
		HDMI (2D)	720x486/59.94i, 720x576/50i	



H/W Model Name		Interface	Supported Format	Description
	In	HDMI (3D)	1920x1080/59.94i, 50i 1280x720/59.94p, 50p	
	In	S-Video & Composite	720x486/59.94i, 720x576/50i	
		SDI (2D)	2048x1556/25p, 24p, 23.98p 1920x1080/59.94i, 50i 1920x1080/59.94p, 50p, 29.97p, 25p, 24p, 23.98p 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	Audio Ch13-16 cannot be output.
DeckLink HD Extreme		SDI (3D)	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p	Audio Ch13-16 cannot be output. Time code can't be output with all formats.
3D / 3D+	Out	HDMI (2D)	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
		HDMI (3D)	1920x1080/29.97p, 25p, 24p, 23.98p	
		Component	1920x1080/29.97p, 25p, 24p, 23.98p 720x486/59.94i 1920x1080/59.94i, 50i 1280x720/59.94p, 50p	
		S-Video & Composite	720x486/59.94i, 720x576/50i	
DeckLink Duo	ln	SDI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i	
Decklink Duo	Out	SDI	1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
D 11:10 1	ln	SDI	1920x1080/29.97p, 25p, 24p, 23.98p	
DeckLink Quad	Out	SDI	1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	



H/W Model Name	H/W Model Name		Supported Format	Description
		SDI (2D)	3840x2160/29.97p*1, 25p, 24p*1, 23.98p*1 1920x1080/59.94p*2, 50p*2, 29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	*1 Only Dual-link connection is supported (6G-SDI is not supported).  *2 Time code can't be fed while capturing.
		SDI (3D)	1920x1080/29.97p, 25p, 24p, 23.98p*3 1920x1080/59.94i, 50i 1280x720/59.94p, 50p	*3 Time code can't be fed while capturing.
	In	HDMI (2D)	3840x2160/29.97p, 25p, 24p, 23.98p	Max audio channel is 2ch.
		HDMI (3D)	Not supported	
		Component	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p	
		S-Video & Composite	Not supported	
DeckLink 4K Extreme		SDI (2D)	3840x2160/29.97p 1920x1080/59.94p, 50p, 29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	Audio Ch13-16 cannot be output.
		SDI (3D)	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p	Audio Ch13-16 cannot be output. Time code can't be output with all formats.
	Out	HDMI (2D)	3840x2160/29.97p, 25p, 24p, 23.98p	Max audio channel is 2ch.
		HDMI (3D)	3840x2160/29.97p*4, 25p*4, 24p*4, 23.98p 1920x1080/59.94p*2, 50p*2, 29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p	*4 Max audio channel is 2ch.
		Component	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p	
		S-Video & Composite	Not supported	



H/W Model Name		Interface	Supported Format	Description
		HDMI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	-HD video only supports 8bit depth
	In	Component	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
Intensity Pro		S-Video & Composite	720x486/59.94i 720x576/50i	
Intensity Pro	Out	HDMI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	HD video only supports 8bit depth
		Component	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
		S-Video & Composite	720x486/59.94i 720x576/50i	
		HDMI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 720x486/59.94i 720x576/50i	
	In	Component	1920x1080/29.97p, 25p, 24p, 23.98p 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
Intensity Shuttle for USB 3.0		S-Video & Composite	Not supported	
		HDMI	1920x1080/29.97p*1, 25p*2, 24p, 23.98p 1920x1080/59.94i,	*1 Output as 59.94i video.
	Out	Component	50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	*2 Output as 50i video.
		S-Video & Composite	Not supported	



H/W Model Name		Interface	Supported Format	Description	
		HDMI	1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	-HD video only supports 8bit depth	
	In	Component	1280x720/59.94p, 50p 720x486/59.94i 720x576/50i		
Intensity Extreme		S-Video & Composite	720x486/59.94i 720x576/50i		
intensity Extreme		HDMI	1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	HD video only supports 8bit depth	
	Out	Component	1920x1080/59.94i, 50i  1280x720/59.94p, 50p 720x486/59.94i  720x576/50i	The video only supports out depth	
		S-Video & Composite	720x486/59.94i 720x576/50i		
	In	SDI	1920x1080/59.94i*, 50i* 720x486/59.94i 720x576/50i	*Time code can't be fed.	
UltraStudio SDI	Out	SDI	1920x1080/59.94i, 50i 720x486/59.94i 720x576/50i	Time code can't be output.	
	Out	HDMI	1920x1080/59.94i, 50i 720x486/59.94i 720x576/50i	Audio channel is inverted.	
		SDI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i		
UltraStudio Pro	In	HDMI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i		
	"'	Component	1280x720/59.94p, 50p 720x486/59.94i 720x576/50i		
			S-Video & Composite	720x486/59.94i 720x576/50i	



H/W Model Name		Interface	Supported Format	Description
		SDI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	Time code can't be output
UltraStudio Pro	Out	HDMI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
OlifaStudio F10	Out	Component	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
		S-Video & Composite	720x486/59.94i 720x576/50i	
		SDI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
	In	HDMI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
	"'	Component		
UltraStudio Express		S-Video & Composite	720x486/59.94i 720x576/50i	
OlliaGludio Express		SDI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
	Out	HDMI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i	
	Jul	Component	1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
		S-Video & Composite	720x486/59.94i 720x576/50i	



H/W Model Name		Interface	Supported Format	Description
		SDI (2D)	3840x2160/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1920x1080/59.94p, 50p, 29.97p, 25p, 24p, 23.98p 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
		SDI (3D)	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p	
	ln	HDMI (2D)	1920x1080/59.94p, 50p, 29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
		HDMI (3D)	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p	
		Component	1920x1080/59.94p, 50p, 29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
UltraStudio 4K		S-Video & Composite	720x486/59.94i 720x576/50i	
		SDI (2D)	3840x2160/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1920x1080/59.94p, 50p, 29.97p, 25p, 24p, 23.98p 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
		SDI (3D)	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p	
	Out	HDMI (2D)	1920x1080/59.94p, 50p, 29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
		HDMI (3D)	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p	
		Component	1920x1080/59.94p, 50p, 29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
		S-Video & Composite	720x486/59.94i 720x576/50i	



H/W Model Name		Interface	Supported Format	Description		
UltraStudio Mini	In	In	Is.	SDI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	
Recorder			HDMI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i		
UltraStudio Mini Monitor	Out	SDI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i	Time code can be output in only SD video.		
UltraStudio Mini Monitor Out	HDMI	1920x1080/29.97p, 25p, 24p, 23.98p 1920x1080/59.94i, 50i 1280x720/59.94p, 50p 720x486/59.94i 720x576/50i				