

## **EDIUS 7 Support Information for Matrox NLE Hardware**

\*Please install Matrox Mtx.utils v7.5.1 to use the hardware with EDIUS

Function	MXO2LE	MXO2mini	MXO2	MXO2Rack	Mojito MAX
10-bit depth support	Yes	Yes	Yes	Yes	Yes
2K(2048x1556) support	-	-	-	•	-
4K support	-	-	-	•	-
TC Input	-	-	-	•	-
TC Output	-	-	-	•	-
Capture with ANC data	-	-	-	•	-
Ancillary Data thru out	-	-	-	•	-
Stereoscopic support	-	-	-	•	-
Deck Control Support	-	-	-	•	-
External REF Input	Yes (BB or Tri)	-	Yes (BB or Tri)	Yes (BB or Tri)	Yes (BB or Tri)
Max Audio ch/bit	16ch*2 / 24bit*1	8ch / 24bit*1	16ch*2 / 24bit*1	16ch*2 / 24bit*1	16ch*2 / 24bit*1
Windows 8 support	-	-	-		-

<sup>\*1</sup> Max audio channel vary depending on I/O port type

## NOTE:

- EDIUS needs to be updated to Version 7.3 or later to use MXO2, MXO2 Rack or Mojito MAX.
- MAX H.264 hardware encoder function not supported.

<sup>\*2 16</sup>ch is only supported in SDI embedded output



## **EDIUS 7 Supported Format for Matrox Hardware**

H/W Model Name		Video		Audio	
H/VV Model Na	ame	Interface	Supported Format	Available Interface & Max Audio Ch	
		SDI	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	SDI embedded: 8ch Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	
	In	HDMI	1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p	HDMI embedded: 8ch Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	
		Component	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	
MXO2LE		S-Video & Composite	720x486/59.94i, 720x576/50i	Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	
	Out	SDI	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	SDI embedded: 16ch Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	
		HDMI	1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p	HDMI embedded: 8ch Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	
		Component	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	
		S-Video & Composite	720x486/59.94i, 720x576/50i	Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	



H/W Model Name		Video		Audio	
		Interface	Supported Format	Available Interface & Max Audio Ch	
	In	HDMI	1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p	HDMI embedded: 8ch Unbalanced Analog Audio: 2ch	
		Component	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94i, 720x576/50i	Unbalanced Analog Audio: 2ch	
MXO2 Mini		S-Video & Composite	720x486/59.94i, 720x576/50i	Unbalanced Analog Audio: 2ch	
WIAGZ WIITII	Out	HDMI	1920x1080/29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p	HDMI embedded: 8ch Unbalanced Analog Audio: 2ch	
		Component	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94i, 720x576/50i	Unbalanced Analog Audio: 2ch	
		S-Video & Composite	720x486/59.94i, 720x576/50i	Unbalanced Analog Audio: 2ch	



H/W Model Name		Video		Audio	
1 I/ W WOUGH IN	iiiie	Interface	Supported Format	Available Interface & Max Audio Ch	
	In	SDI	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	SDI embedded: 8ch AES/EBU: 2ch Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	
		HDMI	1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p	HDMI embedded: 8ch AES/EBU: 2ch Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	
		Component	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	AES/EBU: 2ch Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	
MXO2		S-Video & Composite	720x486/59.94i, 720x576/50i	AES/EBU: 2ch Balanced Analog Audio: 2ch Unbalanced Analog Audio: 2ch	
	Out	SDI	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	SDI embedded: 16ch AES/EBU: 2ch Balanced Analog Audio: 4ch Unbalanced Analog Audio: 6ch	
		HDMI	1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p	HDMI embedded: 8ch AES/EBU: 2ch Balanced Analog Audio: 4ch Unbalanced Analog Audio: 6ch	
		Component	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	AES/EBU: 2ch Balanced Analog Audio: 4ch Unbalanced Analog Audio: 6ch	
		S-Video & Composite	720x486/59.94i, 720x576/50i	AES/EBU: 2ch Balanced Analog Audio: 4ch Unbalanced Analog Audio: 6ch	



H/W Model Name		Video		Description	
m/vv iviodei iva	anne	Interface	Supported Format	Available Interface & Max Audio Ch	
	In	SDI	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i 1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p	SDI embedded: 8ch AES/EBU: 2ch Balanced Analog Audio: 2ch	
		HDMI		HDMI embedded: 8ch AES/EBU: 2ch Balanced Analog Audio: 2ch	
		Component	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	Balanced Analog Audio: 2ch	
MXO2 Rack		S-Video & Composite	720x486/59.94i, 720x576/50i	Balanced Analog Audio: 2ch	
IMAO2 RACK	Out	SDI	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	SDI embedded: 16ch AES/EBU: 2ch Balanced Analog Audio: 2ch	
		HDMI	1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p	HDMI embedded: 8ch AES/EBU: 2ch Balanced Analog Audio: 2ch	
		Component	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	Balanced Analog Audio: 2ch	
		S-Video & Composite	720x486/59.94i, 720x576/50i	Balanced Analog Audio: 2ch	



H/W Model Na	ame	Interface	Supported Format	Description	
		SDI	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	SDI embedded: 8ch AES/EBU: 2ch Balanced Analog Audio: 2ch	
	In	HDMI	1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p	HDMI embedded: 8ch AES/EBU: 2ch Balanced Analog Audio: 2ch	
		Component	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	AES/EBU: 2ch Balanced Analog Audio: 2ch	
		S-Video & Composite	720x486/59.94i, 720x576/50i	AES/EBU: 2ch Balanced Analog Audio: 2ch	
Mojito MAX	Out	SDI	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	SDI embedded: 16ch AES/EBU: 2ch Balanced Analog Audio: 4ch Unbalanced Analog Audio: 2ch	
		HDMI	1920x1080/30, 29.97, 25, 24, 23.98p 1920x1080/59.94, 50i 1280x720/59.94, 50p	HDMI embedded: 8ch AES/EBU: 2ch Balanced Analog Audio: 4ch Unbalanced Analog Audio: 2ch	
		Component	1920x1080/30, 29.97, 25, 24, 23.98PsF 1920x1080/59.94, 50i 1280x720/59.94, 50p 720x486/59.94, 720x576/50i	AES/EBU: 2ch Balanced Analog Audio: 2ch	
		S-Video & Composite	720x486/59.94i, 720x576/50i	AES/EBU: 2ch Balanced Analog Audio: 2ch	